



## Deep-Access Wedge-Wedge Bonder 5832

### Bond System

Wire types	Aluminium and gold wire 17,5-75µm on 2" spool Ribbon from 30x12,5µm to 250x25µm
Bondhead	Wedge-Wedge for Ribbon and thin wire Standard wedges of 1" length, (¾" optional) Motorized wire spool (optional)
Ultrasonic System	F&S Generator 100 kHz (optional 65, 120, 140kHz)

### Bonder Base

#### Axes

- Working area X/Y-axis 200 x 150 mm;
- Programmable step resolution 1 µm
- Programmable Z axis with 100 mm stroke;

#### Hardware

- Dual-Core PC with Windows OS, Ethernet,
- USB 2.0/3.0, Colour Display 22"
- GigE-CCD-Colour Camera, 5 Mpixel
- Fully networkable in TCP/IP servers

#### Software

- From single bonds up to complex programmes,
- Loop shapes can be stored in libraries
- Optional pattern recognition

#### Control

- high-performance embedded ARM-System with Real-time operating system for precision
- 1 wire / second

**Placement accuracy:** +/- 5µm @ 3 sigma, incl. Tool / no wire on F & S Bondtec standard substrate

**Repeatability:** +/- 3 µm @ 3 sigma, incl. Tool / without wire on F & S Bondtec standard substrate

**Loop height accuracy:** +/- 5µm @ 3 sigma, for thin wire 5830 with 25µm aluminum wire on F & S Bondtec standard substrate

### The 58xx series:

The Deep-Access Wedge-Wedge version of the automatic wire bonders in our Series 58xx featuring exchange able bond heads.

A fully automatic mode makes it ideally suited for medium-scale production. Parts to be bonded are fed manually by the operator, but the bonds are produced completely without operator influence.

Thanks to the built-in pattern recognition. Single bonds can be made within seconds, making the machine perfect for R&D, Pilot manufacturing and middle volume production.


# BONDING THE STARS



- Dimensions WxDxH 92x71x65 cm, weight approx. 80 kg
- Connections 100-240 VAC, 1 Phase, 50/60 Hz, max 230 VA  
Ø 6 mm standard vacuum tubing
- Heater controller Integrated in the machine 0-250°C

## Workholder

Standard-Workholder  
for parts up to 8x6"  
with Vacuum and mechanical clamping



## Optional:



6x6" workholder with Vacuum and mechanical clamping



TO Workholder with mechanical clamping



4x4" workholder with rubberized surface and mechanical clamping

### F&S Bondtec Semiconductor GmbH

Industriezeile 49a  
A-5280 Braunau am Inn  
Tel.: +43-7722-67052-8270  
Fax: +43-7722-67052-8272  
Mail: [info@fsbondtec.at](mailto:info@fsbondtec.at)  
Web: [www.fsbondtec.at](http://www.fsbondtec.at)

